

DT-5302 DMM with Kelvin(4-wire) small resistance measurement

- Four terminal Kelvin measurement
- 4000 counts 3 1/4 digital LCD display with backlight
- High resolution to 0.1mΩ with test current to 200mA
- Low battery indication
- Over load protection on all ranges

Features

High accuracy, high resolution portable Milliohm Meter or field use
 Digital 4000 counts display
 Safety design
 Relative zero & Data Hold
 MAX/MIN recording mode
 Auto Power Off
 400mΩ Low Resistance & Wide 40mF capacitance range
 Diode Check & Continuity Test

Specifications

Function	Max. Range	Basic Accuracy
Low Resistance	400mΩ, 4Ω, 40Ω	±(1.0%+5d)
Voltage DC	1000 V	±(1.0%+2d)
Voltage AC	1000V	±(1.2%+5d)
Current DC	400mA	±(1.0%+2d)
Current AC	400mA	±(1.2%+5d)
Resistance	40MΩ	±(1.0%+5d)
Capacitance	40mF	±(3.0%+10d)

Size(HxWxD): 200mm x 92mm x 50mm
 Weight: 582g

Accessories:
 Rubber holster, 4-wire cable, 6 x1.5V "AA" batteries,
 test leads, gift box with carrying case.

- Double molded plastic housing
- CAT III 1000V



EMC & LVD
 EN: 61326
 EN: 61010-1
 EN: 61010-02-032
 EN: 61010-02-033



Model 5302

