

METRAOHM 10

Low-Impedance Measuring Instrument

3-447-117-03
1/2.24

- Low-impedance measuring instrument for protective conductors and equipotential bonding conductors
- 200 mA measurement via battery supply
- 10 A measurement via mains supply
- Graphic colour display
- 4 mm safety measuring sockets
- Integrated memory
- USB port
- Software tool for reading out measured values



Applications

METRAOHM 10 is a low-impedance measuring instrument for protective conductors and equipotential bonding conductors. It is designed to perform two different measurement types:

- R_{LO} four-wire measurement with current 10 A AC
- R_{LO} two-wire measurement with current 200 mA DC
- Contact resistances on lightning protection and grounding systems in accordance with DIN 18014
- Low-resistance continuity on machines in accordance with EN 60204-1 (VDE 0113-1)

Features

- Easy to handle device
- Simple operation with pushbuttons
- Rugged plastic housing
- 200 mA measurement in auto mode or continuous mode
- 10 A measurement in auto mode or manual mode
- Measuring resistance for checking the Kelvin clips and determining the offset values
- Data export to PC (Microsoft Excel-files)
- Data evaluation via software

METRAOHM 10

Low-Impedance Measuring Instrument

Technical Data

Mechanical Design

Housing (W × H × D)	approx. 25 cm × 10.7 cm × 13.5 cm
Weight	approx. 1.75 kg (with batteries, without cables)
Display	TFT LCD display, 480 × 320, 3.5"

Ambient Conditions

Operating temperature	+0 ... +40 °C
Storage temperature	-10 ... +70 °C (without batteries)
Relative humidity	max. 80%, no condensation allowed
Elevation	max. 2000 m
Place of use	Indoor use only

Power Supply

Battery	6 × LR6 AA alkaline battery Voltage: 1.5 V
Mains power supply	230 V _{AC} 50 Hz

Electrical Safety

Measuring category	Cat II / 600 V
Pollution degree	2
Protection category	Cat II
Fuses	F1 (10 A measurement): 10 A / 600 V, 6.3 mm × 32 mm F2 (200 mA measurement): 400 mA / 600 V, 6.3 mm × 32 mm F3 (mains): 315 mA / 250 V, 5 mm × 20 mm

Data Interfaces

Connection	COM Port USB Type B
------------	---------------------

Features Included

- R_{LO} four-wire measurement with current 10 A_{AC}
- R_{LO} two-wire measurement with current 200 mA_{DC}

Relevant Standards

The instrument has been manufactured and tested in accordance with the following safety regulations:

DIN EN 61010-1 IEC 61010-1	Safety requirements for electrical equipment for measurement, control and laboratory use – Part 1: General requirements
IEC/EN 61557-1	Electrical safety in low voltage distribution systems up to 1000 V _{AC} and 1500 V _{DC} – Equipment for testing, measuring or monitoring of protective measures – Part 1: General requirements
IEC/EN 61557-4	Electrical safety in low voltage distribution systems up to 1000 V _{AC} and 1500 V _{DC} – Equipment for testing, measuring or monitoring of protective measures – Part 4: Resistance of earth connection and equipotential bonding
DIN EN IEC 61326-1	Electrical equipment for measurement, control and laboratory use - EMC requirements – Part 1: General requirements
DIN EN 60529 IEC 60529	Test instruments and test procedures Degrees of protection provided by enclosures (IP code)

Characteristic Values

R _{LO} 200 mA (Auto mode)	
Measuring range	0.01 ... 9.99 Ω
	10.0 ... 99.9 Ω
Resolution	0.01 Ω
	0.1 Ω
Accuracy	± (2 % m.v. + 2 dgt)
Test current	> 200 mA _{DC} for R ≤ 5 Ω (including compensation value)
Test current resolution	1 mA
Open circuit voltage	4 V ≤ V ₀ ≤ 12 V _{DC}
Measurement method	2 wires
Standard	IEC/EN 61557-4 (for R > 0.10 Ω)

METRAOHM 10

Low-Impedance Measuring Instrument

R_{LO} 200 mA (Continuous mode)	
Measuring range	0.01 ... 9.99 Ω
	10.0 ... 99.9 Ω
Resolution	0.01 Ω
	0.1 Ω
Accuracy	± (2 % m.v. + 2 dgt)
Test current	> 200 mA _{DC} for R ≤ 5 Ω (including compensation value)
Test current resolution	1 mA
Open circuit voltage	4 V ≤ V ₀ ≤ 12 V _{DC}
Measurement method	2 wires
Continuous mode	Cont+ (R+) and Cont- (R-)
Duration of continuous test	1 ... 15 s
Standard	IEC/EN 61557-4 (for R > 0.10 Ω)

R_{LO} 10 A Limit MAN	
Measuring range	0.001 ... 0.999 Ω
Resolution	0.001 Ω
Accuracy	± (1 % m.v. + 2 dgt)
Test current	> 10 A _{AC} for R ≤ 0.45 Ω
Test current resolution	0.1 A
Open circuit voltage	V ₀ ≤ 12 V _{AC}
Measurement method	4 wires
Power supply	230 V AC 50 Hz
Standard	IEC/EN 61439-1

R_{LO} 10 A Limit AUTO	
Measuring range	0.001 ... 0.999 Ω
Resolution	0.001 Ω
Accuracy	± (1 % m.v. + 2 dgt)
Test current	> 10 A _{AC} for R ≤ 0.45 Ω
Test current resolution	0.1 A

Open circuit voltage	V ₀ ≤ 12 V _{AC}
Measurement method	4 wires
Selectable section	0.5, 1.0, 1.5, 2.5, 4.0, 6.0, 10 and 16 mm ² (ρ[Cu] = 0.017 Ω mm ² /m)
Length measuring range	0.1 m ... 999.9 m
Power supply	230 V _{AC} 50 Hz
Standard	IEC/EN 60204-1

Scope of Delivery

- 1 METRAOHM 10 (M630K)
- 1 AC mains power supply cable
- 1 USB type A to type B cable
- 1 Two-wire measurement standard test leads with alligator clips
- 1 Four-wire Kelvin test leads with alligator clips
- 1 Kelvin clip test 1 Ω / 25 W (Z630K)
- 1 Carrying case with carrying strap and strap on the instrument
- 1 Test report
- 1 Calibration certificate

Order Information

Description	Type	Article number
METRAOHM 10	Low-Impedance Measuring Instrument	M630K

For additional information regarding accessories please refer to

- Measuring Instruments and Testers catalog
- www.gossenmetrawatt.com

© Gossen Metrawatt GmbH

Prepared in Germany • Subject to change, errors excepted • PDF version available on the Internet

All trademarks, registered trademarks, logos, product names, and company names are the property of their respective owners.

Gossen Metrawatt GmbH
Südwestpark 15
90449 Nürnberg
Germany

Telefon +49 911 8602-0
Telefax +49 911 8602-669
E-Mail info@gossenmetrawatt.com
www.gossenmetrawatt.com