

DT-926A/926B/926/927A/927/927H/928BT Compact True RMS Multimeter with Battery test



Bluetooth
Meterbox Pro

• Double molded plastic housing

• True RMS

927 compact 600V True RMS 13-function auto-ranging multimeter with built-in NCV and Live detector.

926 is durable and attractive 600V multimeter for the beginning electrician. 7 Measurement functions including AC and DC voltage, DC current, resistance, diode test, battery test, and continuity provide the capability to tackle any basic electrical task.

	GOOD	LOW	BAD
1.5V	>1.3V	0.95 to 1.3V	<0.95V
9V	>7.7V	5.7 to 7.7V	<5.7V



EMC & LVD
EN: 61326
EN: 61010-1
EN: 61010-02-032
EN: 61010-02-033



Model 926B



Model 927



Model 928BT

Features

	926A	926B	926	927A	927	927H	928BT
Digital display counts with backlit	2000	2000	2000	4000	4000	6000	6000
True RMS measurement	*		*	*	*	*	*
Range selection	Manual	Manual	Manual	Auto	Auto	Auto	Auto
MAXMIN hold				*	*	*	*
0.1~99.9% Duty Cycle measurement					*	*	*
Diode & Continuity buzz check	*	*	*	*	*	*	*
Auto Power Off	*		*	*	*	*	*
Display backlight				*	*	*	*
Data Hold/REL measurement	*	*/-	*	*	*	*	*
Fast and accurate capacitance measurement					*		
Non-Contact ACV & ACV Live detection				NCV	*	*	*
Backlight for LCD, Knob Switch, Flashlight					*	*	*
1.5V and 9V battery test	*	*	*		*		
Full ranges protection	*	*	*	*	*	*	*
Drop tested up to 2 meters	*	*	*	*	*	*	*
Square wave signal output						*	*
Low input Impedance (around 3kΩ)						*	*
Bluetooth interface with Meterbox Pro software							*

Specifications

Function	Max Range	Basic Accuracy	926A	926B	926	927A	927	927H	928BT
Voltage DC	600V	±0.5%	*	*	*	*	*	*	1000V
Voltage AC	600V	±1.2%	*	*	*	*	*	*	1000V
Current DC	10A	±1.5%	*	*	*	*	*	*	*
Current AC	10A	±2.0%	*	*	*	*	*	*	*
Resistance	2MΩ	±0.8%	*	*	*				
	40MΩ	±3.0%				*	*	60MΩ	60MΩ
Capacitance	100mF	±3.5%				4mF	*	*	*
Frequency	10MHz	±1.5%				*	*	10KHz	10KHz
Temperature	760°C/1400°F	±1.5%				*	*	*	*
Battery test	Test 1.5V and 9V batteries		*	*	*		*		
Diode Check			*	*	*	*	*	*	*
Continuity Test			*	*	*	*	*	*	*

Size(HxWxD): 151mm x 75mm x 45mm Weight: 255g

Accessories: Test leads, 2x1.5V batteries and type K temperature probe (927/927A/927H/928BT), clamshell.



Meterbox Pro